

BRAVO Power-Foam Heavy Duty Stripper for Spot Buildups

| HMIS | | NFPA | Personal protective equipment | | |
|-------------------------------|---|------|-------------------------------|--|--|
| Health | 3 | 3 | and some | | |
| Flammability | 4 | 4 | | | |
| Physical Hazard / Instability | 0 | 0 | | | |

Version Number: 1 Preparation date: 2013-02-05

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BRAVO Power-Foam Heavy Duty Stripper for Spot Buildups

MSDS #: MS0300787 **Product Code**: MS0300787

Recommended use: • Industrial/Institutional

Floor care

Manufacturer, importer, supplier:Canadian HeadquartersUS HeadquartersDiversey, Inc. - CanadaDiversey, Inc.2401 Bristol Circle8310 16th St.Oakville, Ontario L6H 6P1Sturtevant, Wisconsin 53177-1964Phone: 1-800-668-3131

Phone: 1-888-352-2249

MSDS Internet Address: www.diversey.com

Emergency telephone number: 1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER. CORROSIVE. CAUSES SKIN AND EYE BURNS. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE.

Principal routes of exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Eye contact: Corrosive. Causes permanent eye damage, including blindness.

Skin contact: Corrosive. Causes permanent damage.

Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract.

Ingestion: Corrosive. Causes burns to mouth, throat and stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Ingredient(s) | CAS# | Weight % | LD50 Oral - Rat (mg/kg) | LD50 Dermal - Rabbit | LC50 Inhalation - Rat |
|-------------------------------|-----------|------------|----------------------------|-------------------------|----------------------------------|
| Benzyl alcohol | 100-51-6 | 0.1 - 1.5% | 1230 | 2000 mg/kg | 8.8 mg/L (4 h) |
| 2-butoxyethanol | 111-76-2 | 1 - 5% | 1400 | 220 mg/kg | 2.21 mg/L (4 h) 450 ppm (4 h) |
| Diethylene glycol butyl ether | 112-34-5 | 1 - 5% | 4500 | 2700 mg/kg | Not available |
| Potassium hydroxide | 1310-58-3 | 1 - 5% | 273 | Not available | Not available |
| Monoethanolamine | 141-43-5 | 1 - 5% | 1720 | 1 mL/kg 1025 mg/kg | Not available |
| Isobutane | 75-28-5 | 5 - 10% | Not available | Not available | 658 mg/L (4 h) |

4. FIRST AID MEASURES

Eye contact: Immediately flush eyes with running water for 15-20 minutes, keeping eyelids open. Get medical

attention immediately.

Skin contact: Immediately flush with plenty of water for 15-20 minutes . Get medical attention immediately.

Inhalation: If breathing is affected, remove to fresh air. Get medical attention immediately.

Ingestion: If swallowed, rinse mouth. Give a cupful of water or milk. THEN IMMEDIATELY CONTACT A

PHYSICIAN OR POISON CENTER. DO NOT induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person.

Aggravated Medical Conditions: Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc.,

may be more susceptible to irritating effects

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Use dry chemical, CO2, water spray or "alcohol" foam.

Specific hazards: Aerosol product - Containers may rocket or explode in heat of fire. NFPA 30B Level 1 Aerosol

Unusual hazards: Corrosive material (See sections 8 and 10).

Specific methods: Aerosol Product - Containers may rocket or explode in heat of fire. Use water spray to keep

fire-exposed containers cool.

Autoignition temperature: No information available.

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Put on appropriate personal protective equipment (see Section 8.).

Environmental precautions and clean-up methods: Clean-up methods - large spillage. Remove all sources of ignition. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Use a water rinse for final

clean-up.

7. HANDLING AND STORAGE

Handling:

Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Do not let product overspray on to the floor as the product's ingredients could make the floor slippery. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage:

NFPA 30B Level 1 Aerosol . Protect from freezing. Store in a cool, dry, well ventilated area away from heat or open flame. Do not pierce or burn, even after use . KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection: Chemical-splash goggles. **Hand protection:** Chemical-resistant gloves

Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear. **Respiratory protection:** In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program

that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever

workplace conditions warrant a respirator's use.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice

| Ingredient(s) | CAS# | ACGIH | OSHA | Mexico |
|---------------------|-----------|-----------------------------|---|---|
| 2-butoxyethanol | 111-76-2 | 20 ppm (TWA) | Skin 50 ppm (TWA) 240 mg/m³ (TWA) | 75 ppm (STEL) 360 mg/m ³ (STEL) 26 ppm (TWA) 120 mg/m ³ |
| | | | , , | (TWA) |
| Potassium hydroxide | 1310-58-3 | 2 mg/m³ (Ceiling) | | |
| Monoethanolamine | 141-43-5 | 6 ppm (STEL) 3 ppm (TWA) | 3 ppm (TWA) 6 mg/m³ (TWA) | 6 ppm (STEL) 15 mg/m³ (STEL) 3 ppm (TWA) 8 mg/m³ (TWA) |
| Isobutane | 75-28-5 | 1000 ppm (TWA) | | |

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Pressurized Liquid

Appearance: Aerosol Specific gravity: 0.99

Vapor density: No information available Boiling point/range: Not determined

Decomposition temperature: Not determined

Solubility: Completely Soluble

Solubility in other solvents: No information available

Partition coefficient (n-octanol/water): No information available

Elemental Phosphorus: 0.06 % by wt.

pH: 13.0

Flame Extension (inches): 0

Explosion limits: - upper: Not determined - lower: Not determined

Bulk density: No information available Evaporation Rate: No information available

Color: Clear White Odor: Solvent

Melting point/range: Not determined

Autoignition temperature: No information available

Density: 8.26 lbs/gal 0.99 Kg/L Flash point: 19 °F -7.0 °C Viscosity:No information available

VOC: 10.67 % *

Dilution pH: N/A @ RTU

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Stability: The product is stable

Polymerization: Hazardous polymerization does not occur.

Hazardous decomposition products: None known.

Materials to avoid: Acids.

Conditions to avoid: Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: Corrosive. Oral LD50 estimated to be between 2000 - 3000 mg/kg; Dermal LD50 estimated to be >

2000 mg/kg.

Component Information: See Section 3

Chronic toxicity: None known

Specific effects

Carcinogenic effects: None known Mutagenic effects: None known Reproductive toxicity: None known Target organ effects: None known

12. ECOLOGICAL INFORMATION

Environmental Information: No data available

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Dispose of according to all federal, state and local applicable regulations. This product, as sold, if discarded or disposed, is a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Dispose in compliance with all Federal, state, provincial, and local laws and regulations. Use up contents if possible before disposal. If possible, recycle empty aerosol cans to the nearest steel recycling center.

RCRA Hazard Class: D001 Ignitable Waste D002 Corrosive Waste

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Please refer to the Diversey HazMat Library, http://naextranet.diversey.com/dot/, for up to date shipping information.

DOT Bill of Lading Description: LTD. QTY.

IMDG Bill of Lading Description: UN1950, AEROSOLS, 2.2, LTD. QTY.

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

RIGHT TO KNOW (RTK)

| Ingredient(s) | CAS# | MARTK: | NJRTK: | PARTK: | RIRTK: |
|-------------------------------|------------|--------|--------|--------|--------|
| Benzyl alcohol | 100-51-6 | X | ı | X | - |
| 2-butoxyethanol | 111-76-2 | X | X | X | - |
| Diethylene glycol butyl ether | 112-34-5 | = | = | = | - |
| Potassium hydroxide | 1310-58-3 | X | X | X | X |
| Monoethanolamine | 141-43-5 | X | X | X | - |
| Water | 7732-18-5 | - | - | - | - |
| Ethoxylated secondary alcohol | 84133-50-6 | = | = | = | - |
| Isobutane | 75-28-5 | X | X | X | - |

CERCLA/ SARA

| Ingredient(s) | CAS# | Weight % | CERCLA/SARA RQ (lbs) | Section 302 TPQ (lbs) | Section 313 |
|-------------------------------|-----------|----------|----------------------|-----------------------|-------------|
| 2-butoxyethanol | 111-76-2 | 1 - 5% | | | X |
| Diethylene glycol butyl ether | 112-34-5 | 1 - 5% | | | X |
| Potassium hydroxide | 1310-58-3 | 1 - 5% | 1000 | | |

| Ingredient(s) | CAA HAP | CAA ODS | CWA Priority Pollutants |
|-----------------|---------|---------|-------------------------|
| 2-butoxyethanol | X | | |

SARA 311/312 Hazard Categories

Immediate: X
Delayed: Fire: X
Reactivity: Sudden Release of Pressure: X

Canada

WHMIS hazard class: A Compressed gases, E Corrosive material .



16. OTHER INFORMATION

Reason for revision: Not applicable Prepared by: NAPRAC

Additional advice:

• This product has been classified in accordance with hazard criteria of the Controlled Products

Regulations and the MSDS contains all the information required by the Controlled Products

Regulations

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.