# **Datey**®

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Oatey ABS Medium Black Cement

Other means of identification

SDS number 1300E

Recommended use Joining ABS Pipes
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name Oatey Co.

Address 4700 West 160th St.

Cleveland, OH 44135

Telephone 216-267-7100 E-mail info@oatey.com

**Transport Emergency** Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)

Emergency First Aid 1-877-740-5015
Contact person MSDS Coordinator

# 2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2A

Not classified.

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, single exposure

Category 3 narcotic effects

Aspiration hazard Category 1

OSHA defined hazards

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes serious

eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

**Precautionary statement** 

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only outdoors or in a

well-ventilated area. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash

thoroughly after handling. Wear protective gloves/eye protection/face protection.

**Response** Do NOT induce vomiting. If eye irritation persists: Get medical advice/attention. In case of fire:

Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations. **Hazard(s) not otherwise** Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

classified (HNOC)

Supplemental information

Not applicable.

Oatey ABS Medium Black Cement SDS US

927420 Version #: 01 Revision date: 12-1-2017 Issue date: 5-27-2015

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	CAS number	%
Methyl ethyl ketone	78-93-3	40-60
ABS Resin	9003-56-9	30-40
Acetone	67-64-1	10-20
Other components below reportable levels		2.41

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Take off immediately all contaminated clothing. Wash off with soap and water.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Call a physician or poison control center immediately. Do not induce vomiting. If vomiting occurs, Ingestion

keep head low so that stomach content doesn't get into the lungs. Aspiration may cause

pulmonary edema and pneumonitis.

Most important symptoms/effects, acute and delayed

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a

narcotic effect and may cause headache, fatique, dizziness and nausea.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

**General information** 

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Specific methods General fire hazards In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors or mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Oatey ABS Medium Black Cement SDS US 2/8

## Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

#### **Environmental precautions**

# 7. Handling and storage

# Precautions for safe handling

Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not smoke. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling.

## Conditions for safe storage. including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers.

# 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Methyl ethyl ketone (CAS	PEL	590 mg/m3	
78-93-3)			
		200 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	300 ppm	
·	TWA	200 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Methyl ethyl ketone (CAS 78-93-3)	STEL	885 mg/m3	
·		300 ppm	
	TWA	590 mg/m3	
		200 ppm	

## **Biological limit values**

## **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*

Oatey ABS Medium Black Cement SDS US

#### **ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Methyl ethyl ketone (CAS	2 mg/l	MEK	Urine	*
78-93-3)				

<sup>\* -</sup> For sampling details, please see the source document.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

#### Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear protective gloves.

Other Wear appropriate chemical resistant clothing.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

**General hygiene** considerations

When using, do not eat, drink or smoke.

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.

**Form** Opaque liquid.

Black. Color Solvent. Odor **Odor threshold** Not available. Not available. Melting point/freezing point Not available. Initial boiling point and boiling

range

151 °F (66.11 °C)

14.0 - 23.0 °F (-10.0 - -5.0 °C) Flash point

**Evaporation rate** 5.5 - 8Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

1.8

Flammability limit - upper

11.8

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%)

145 mm Hg @ 20 C Vapor pressure

2.5 Vapor density

0.89 +/- 0.02 Relative density

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available. Not available. **Decomposition temperature** 500 - 1500 cP **Viscosity** 

Oatey ABS Medium Black Cement SDS US Viscosity temperature 77 °F (25 °C)

Other information

**Bulk density** 7.4 lbs/gal

VOC (Weight %) < 325 g/l SQACMD 1168/M316A

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

No dangerous reaction known under conditions of normal use.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Acids. Strong oxidizing agents. Ammonia. Amines. Isocyanates. Caustics. Incompatible materials

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation May be fatal if swallowed and enters airways. Vapors have a narcotic effect and may cause

headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful. May cause

irritation to the respiratory system.

No adverse effects due to skin contact are expected. Skin contact

Eye contact Causes serious eye irritation.

Ingestion May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Symptoms of

overexposure may be headache, dizziness, tiredness, nausea and vomiting.

## Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects. May cause respiratory irritation.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rabbit	20 ml/kg
Inhalation		
LC50	Rat	50 mg/l, 8 Hours
Oral		
LD50	Rat	5800 mg/kg
	Rat	5800 mg/kg

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -Respiratory tract irritation. Narcotic effects.

single exposure

Oatey ABS Medium Black Cement 5/8 927420 Version #: 01 Revision date: 12-1-2017 Issue date: 5-27-2015

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful.

# 12. Ecological information

**Ecotoxicity** 

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Acetone (CAS 67-64-1)

Aquatic

Fish LC50

Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Acetone (CAS 67-64-1) -0.24 Methyl ethyl ketone (CAS 78-93-3) 0.29

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

# 14. Transport information

DOT

UN number UN1133 UN proper shipping name Adhesives

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group ||

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions T11, TP1, TP8, TP27

Packaging exceptions 150
Packaging non bulk 201
Packaging bulk 243

IATA

UN number UN1133 UN proper shipping name Adhesives

UN proper shipping name Transport hazard class(es)

ass(es)

Class 3 Subsidiary risk -

Oatey ABS Medium Black Cement
927420 Version #: 01 Revision date: 12-1-2017 Issue date: 5-27-2015

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

П Packing group **Environmental hazards** No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

**UN** number UN1133 **UN** proper shipping name **ADHESIVES** 

Transport hazard class(es) **Class** 3 Subsidiary risk Ш Packing group **Environmental hazards** 

Marine pollutant No. F-E, S-D **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

# 15. Regulatory information

## **US** federal regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not available.

Not listed.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Acetone (CAS 67-64-1) LISTED Methyl ethyl ketone (CAS 78-93-3) LISTED

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories** Delayed Hazard - No

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

## SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

## Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and **Chemical Code Number**

Acetone (CAS 67-64-1) 6532 Methyl ethyl ketone (CAS 78-93-3) 6714

## Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV Methyl ethyl ketone (CAS 78-93-3) 35 %WV

**DEA Exempt Chemical Mixtures Code Number** 

Acetone (CAS 67-64-1) 6532

SDS US Oatey ABS Medium Black Cement 7/8 927420 Version #: 01 Revision date: 12-1-2017 Issue date: 5-27-2015

## **US** state regulations

## **US. Massachusetts RTK - Substance List**

Acetone (CAS 67-64-1)

Methyl ethyl ketone (CAS 78-93-3)

## US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Methyl ethyl ketone (CAS 78-93-3)

## US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Methyl ethyl ketone (CAS 78-93-3)

#### **US. Rhode Island RTK**

Acetone (CAS 67-64-1)

Methyl ethyl ketone (CAS 78-93-3)

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

Domestic Substances List (DSL)

Australian Inventory of Chemical Substances (AICS)

#### **International Inventories**

Australia

Canada

Country(s) or region

Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

# 16. Other information, including date of preparation or last revision

**Inventory name** 

27-May-2015 Issue date

**Revision date** Version # 01

United States & Puerto Rico

Health: 2 **HMIS®** ratings

Flammability: 3 Physical hazard: 0

NFPA ratings



**Disclaimer** The information in the sheet was written based on the best knowledge and experience currently

available.

927420 Version #: 01 Revision date: 12-1-2017 Issue date: 5-27-2015 8/8

On inventory (yes/no)\*

Yes

Yes

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).