




SAFETY DATA SHEET

1. Product and Company Identification

Product identifier	Evap-Fresh No Rinse Evaporator Cleaner & Disinfectant (4166-75)
Other means of identification	Not available
Recommended use	Cleaner / Disinfectant / Mildewstat / Deodorizer
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Company name	Nu-Calgon
Address	2008 Altom Court St. Louis, MO 63146 United States
Telephone	314-469-7000 / 800-554-5499
E-mail	info@nucalgon.com
Emergency phone number	1-800-424-9300 (CHEMTREC)

2. Hazards Identification

Physical hazards	Gases under pressure	Liquefied gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Specific target organ toxicity, repeated exposure	Category 2
	Not classified.	
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Warning	
Hazard statement	Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure.	
Precautionary statement		
Prevention	Wash thoroughly after handling. Wear protective gloves. Wear eye/face protection. Do not breathe mist or vapor.	
Response	If on skin: Wash with plenty of water. Specific treatment (see this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Get medical advice/attention if you feel unwell.	
Storage	Protect from sunlight. Store in a well-ventilated place.	
Disposal	Dispose of waste and residues in accordance with local authority requirements.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	This is a registered EPA product. The product labeling is in compliance with EPA regulations and guidelines.	

3. Composition/Information on Ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	1-5
Diethylene glycol monobutyl ether		112-34-5	1-5

Chemical name	Common name and synonyms	CAS number	%
Propane		74-98-6	1-5
Tetrasodium ethylenediamine tetraacetate		64-02-8	1-5

Composition comments US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First Aid Measures

Inhalation	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice.
Skin contact	If on skin or clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
Eye contact	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
Ingestion	If swallowed: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.
Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Probable mucosal damage may contraindicate the use of gastric lavage.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire Fighting Measures

Suitable extinguishing media	Alcohol resistant foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	Contents under pressure.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Cool containers exposed to flames with water until well after the fire is out.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Avoid contact with eyes, skin and clothing.
--------------------------------------	--

Conditions for safe storage, including any incompatibilities

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Protect from sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

8. Exposure Controls/Personal Protection

Occupational exposure limits**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Butane (CAS 106-97-8)	STEL	1000 ppm	
Diethylene glycol monobutyl ether (CAS 112-34-5)	TWA	10 ppm	Inhalable fraction and vapor.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3 800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Not available.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Not applicable.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and Chemical Properties

Appearance	Spray
Physical state	Gas Liquid under pressure via propellant.
Form	Aerosol. Liquefied gas.
Color	Clear
Odor	Lemon
Odor threshold	Not available.
pH	12.5
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	Not available.
Specific gravity	1.005 g/mL
Partition coefficient (n-octanol/water)	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Heat of combustion	4.57 kJ/g
VOC (Weight %)	5.0% by weight (US federal, CARB/OTC/LADCO)

10. Stability and Reactivity

Reactivity	Reacts vigorously with acids.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Reacts violently with strong acids. This product may react with oxidizing agents. Do not mix with other chemicals.
Incompatible materials	Oxidizing agents. Acids.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon. Oxides of nitrogen.

11. Toxicological Information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects**Acute toxicity**

Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
Dermal		
LD50	Not available	
Inhalation		
LC50	Mouse	539600 ppm, 120 Minutes, ECHA
		520400 ppm, 120 Minutes, ECHA
		1237 mg/L, 120 Minutes
		680 mg/L, 2 Hours, HSDB
		57 %, 120 Minutes, ECHA
		52 %, 120 Minutes
	Rat	> 800000 ppm, 10 Minutes, ECHA
		1442738 mg/m3, 10 Minutes, ECHA

Components	Species	Test Results
		1354944 mg/m3, 10 Minutes, ECHA
		570000 ppm, 10 Minutes, ECHA
		276000 ppm, 4 Hours, CCOHS
		1443 mg/L, 10 Minutes, ECHA
		1355 mg/L, 10 Minutes
<i>Oral</i> LD50	Not available	
Diethylene glycol monobutyl ether (CAS 112-34-5)		
Acute		
<i>Dermal</i> LD50	Rabbit	2700 mg/kg
<i>Inhalation</i> LC50	Not available	
<i>Oral</i> LD50	Guinea pig	2000 mg/kg
	Mouse	2400 mg/kg
	Rabbit	2200 mg/kg
	Rat	3384 mg/kg
Propane (CAS 74-98-6)		
Acute		
<i>Dermal</i> LD50	Not available	
<i>Inhalation</i> LC50	Mouse	539600 ppm, 120 Minutes, ECHA
		520400 ppm, 120 Minutes, ECHA
		1237 mg/L, 120 Minutes
		57 %, 120 Minutes, ECHA
		52 %, 120 Minutes
	Rat	> 12000000 ppm, 4 hours
		> 800000 ppm, 10 Minutes, ECHA
		> 1464 mg/L, 15 Minutes, HSDB
		1442738 mg/m3, 10 Minutes, ECHA
		1354944 mg/m3, 10 Minutes, ECHA
		570000 ppm, 10 Minutes, ECHA
		1355 mg/L, 10 Minutes
<i>Oral</i> LD50	Not available	
Tetrasodium ethylenediamine tetraacetate (CAS 64-02-8)		
Acute		
<i>Dermal</i> LD50	Not available	
<i>Inhalation</i> LC50	Not available	
<i>Oral</i> LD50	Rat	> 2000 mg/kg, HSDB
		3200 mg/kg, ECHA
		2700 mg/kg, ECHA
		2581 mg/kg, ECHA
		2150 mg/kg, ECHA
		1913 mg/kg, ECHA

Components	Species	Test Results
		1780 mg/kg, ECHA
		1700 mg/kg, ECHA
		1658 mg/kg, LOLI
Skin corrosion/irritation	Causes skin irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Not listed.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not regulated.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard	Not likely, due to the form of the product.	
Chronic effects	Prolonged inhalation may be harmful.	
Further information	Not available.	

12. Ecological Information

Ecotoxicity	See below		
Ecotoxicological data			
Components		Species	Test Results
Diethylene glycol monobutyl ether (CAS 112-34-5)			
Crustacea	EC50	Daphnia	2850 mg/L, 48 Hours
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	1300 mg/L, 96 hours
Tetrasodium ethylenediamine tetraacetate (CAS 64-02-8)			
Algae	EC50	Algae	1.01 mg/L, 72 Hours
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	610 mg/L, 24 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	472 - 500 mg/L, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Partition coefficient n-octanol / water (log Kow)			
Butane		2.89	
Diethylene glycol monobutyl ether		0.56	

Partition coefficient n-octanol / water (log Kow)

Propane

2.36

Mobility in soil	No data available.
Mobility in general	Not available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal Considerations

Disposal instructions	Container Disposal: Nonrefillable container. Do not reuse empty container. Do not puncture or incinerate. IF EMPTY: Place in trash or offer for recycling if available. IF PARTLY FILLED: Call your local waste agency for disposal instructions. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport Information

U.S. Department of Transportation (DOT)**Basic shipping requirements:**

UN number	UN1950
Proper shipping name	Aerosols, non-flammable, (each not exceeding 1 L capacity)
Hazard class	Limited Quantity - US
Packaging exceptions	<1L - Limited Quantity
Packaging non bulk	None
Packaging bulk	None

IATA/ICAO (Air)**Basic shipping requirements:**

UN number	UN1950
Proper shipping name	Aerosols, non-flammable
Hazard class	Limited Quantity - IATA
	<1L - Limited Quantity

IMDG (Marine Transport)**Basic shipping requirements:**

UN number	UN1950
Proper shipping name	AEROSOLS
Hazard class	Limited Quantity - IMDG
	<1L - Limited Quantity

DOT; IMDG



15. Regulatory Information

US federal regulations

This is an EPA registered product. This material can only be used commercially in the EPA registered application(s) noted on the product label.
EPA Reg. # 1839-84-65516

PRECAUTIONARY STATEMENTS: HAZARDS TO HUMANS AND DOMESTIC ANIMALS.
WARNING

KEEP OUT OF THE REACH OF CHILDREN. Causes eye and skin irritation. Do not get in eyes, on skin or on clothing. Harmful if swallowed. Avoid contamination of food. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

Contents under pressure. Do not puncture. Do not use or store near open flame. Exposure to temperatures above 130°F may cause bursting. Never throw container into fire or incinerator.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Butane (CAS 106-97-8)	Listed.
Diethylene glycol monobutyl ether (CAS 112-34-5)	Listed.
Propane (CAS 74-98-6)	Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes
	Delayed Hazard - No
	Fire Hazard - No
	Pressure Hazard - Yes
	Reactivity Hazard - No

SARA 302 Extremely hazardous substance	No
---	----

SARA 311/312 Hazardous chemical	No
--	----

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Diethylene glycol monobutyl ether	112-34-5	1-5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Diethylene glycol monobutyl ether (CAS 112-34-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)
Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA)	Not regulated.
---------------------------------------	----------------

Food and Drug Administration (FDA)	Not regulated.
---	----------------

US state regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

US - Illinois Chemical Safety Act: Listed substance

Butane (CAS 106-97-8)
Diethylene glycol monobutyl ether (CAS 112-34-5)
Propane (CAS 74-98-6)

US - Louisiana Spill Reporting: Listed substance

Butane (CAS 106-97-8)	Listed.
Diethylene glycol monobutyl ether (CAS 112-34-5)	Listed.

Propane (CAS 74-98-6) Listed.
US - Minnesota Haz Subs: Listed substance
 Butane (CAS 106-97-8) BUTANE
 Propane (CAS 74-98-6) PROPANE

US - New Jersey RTK - Substances: Listed substance
 Butane (CAS 106-97-8)
 Diethylene glycol monobutyl ether (CAS 112-34-5)
 Propane (CAS 74-98-6)

US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant
 Propane (CAS 74-98-6)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)
 Not listed.

US. Massachusetts RTK - Substance List
 Butane (CAS 106-97-8)
 Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act
 Butane (CAS 106-97-8)
 Diethylene glycol monobutyl ether (CAS 112-34-5)
 Propane (CAS 74-98-6)

US. Pennsylvania RTK - Hazardous Substances
 Butane (CAS 106-97-8)
 Diethylene glycol monobutyl ether (CAS 112-34-5)
 Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law
 Butane (CAS 106-97-8)
 Diethylene glycol monobutyl ether (CAS 112-34-5)
 Propane (CAS 74-98-6)

US. Rhode Island RTK
 Butane (CAS 106-97-8)
 Diethylene glycol monobutyl ether (CAS 112-34-5)
 Propane (CAS 74-98-6)

US. California Proposition 65


This product is not subject to warning labeling under the California Proposition 65 regulation.

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)		

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 3
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 20-June-2017
Revision date 20-June-2017
Version # 02

Further information For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Prepared by Nu-Calgon Technical Service Phone: (314) 469-7000