

Material Safety Data Sheet

MANUFACTURER:

GPM

201 Jandus Road

Cary, IL 60013

EMERGENCY TELEPHONE NUMBER:

(866)257-3981

DATE: September 15, 2015

TECHNICAL INFORMATION:

(847)639-5383

SUPERSEDES: July 09, 2013

HMIS:

H *[2]

F [4]

R [0]

SECTION 1- PRODUCT IDENTIFICATION

PRODUCT CODE: PDS-90, 94

PRODUCT NAME: Premium Décor Metallic Spray

PRODUCT CLASS: Aerosol Paint

SECTION 2 - HAZARDOUS INGREDIENTS

INGREDIENT	CAS NUMBER	WT. %	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE mmHg@20°C
			TLV	PEL	
Propane/n-Butane Blend	68476-86-8	31-33	1000ppm	1000ppm	80 p.s.i.
(S)Toluene	108-88-3	31-36	20ppm	100ppm	22.0
Acetone	67-64-1	10-14	750ppm	1000ppm	186.0
(S)Xylene	1330-20-7	0.9-3	100ppm	100ppm	14.0
(S)Ethyl Benzene	100-41-4	0.3-0.8	100ppm	100ppm	12.0
(S)Aluminum Pigment	7429-90-5	2-5	10mg/m ³	10 mg/m ³	NA
Linseed Oil	67746-08-1	2-5	NA	NA	NA

(S) - This ingredient is subject to the reporting requirements of Section 313 SARA Title III.

NA - Not applicable.

NE - Not established.

SECTION 3 - PHYSICAL DATA

VAPOR DENSITY: [X] HEAVIER [] LIGHTER THAN AIR

EVAPORATION RATE: [] FASTER [X] SLOWER THAN ETHER

APPEARANCE/ODOR: Silver liquid/solvent

VOLATILE ORGANIC COMPOUND(VOC) MAXIMUM: Metallic 80 % MIR: 1.90

BOILING RANGE: <0°F

80-86% VOLATILE VOLUME

DENSITY: 6.2-6.4 Wt(lbs)/Gal

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: OSHA Class IA

DOT ORM-D

FLASH POINT: <-138°F LEL: 2.0

EXTINGUISHING MEDIA:

[X] FOAM [] ALCOHOL FOAM [X] CO₂ [X] DRY CHEMICAL [X] WATER FOG [] OTHER

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may explode when exposed to extreme heat. Isolate from heat, sparks and open flame. Vapors may accumulate and travel to ignition sources distant from handling site.

SPECIAL FIRE FIGHTING PROCEDURES: Use a self-contained breathing apparatus with full face mask in a positive pressure demand mode. Treat as a volatile liquid fire. Water spray may be ineffective. If water spray is used, fog nozzles are preferable. Water may be used to cool sealed containers to prevent pressure build-up and possible explosion or auto-ignition when exposed to the heat of a fire.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide and unidentified organic compounds.

SECTION 5 - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

INHALATION: Exposure to vapors, mists, or sanding dusts may cause moderate irritation to the lungs, nose, and throat. May also cause dizziness, nausea, fatigue, or headache.

SKIN CONTACT: Exposure may cause mild irritation. Prolonged exposure may cause drying and cracking.

EYE CONTACT: Causes irritation, including redness, stinging and watering.

INGESTION: Moderately toxic in large amounts. Could cause drowsiness, nausea or headache. (See additional information in Section 9)

CARCINOGENICITY: This product contains ethyl benzene (see section 2). Ethyl benzene has been classified by IARC (not NTP or OSHA) as a possible carcinogen for humans (2B) from lab animal studies.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Preexisting skin, eye and respiratory disorders may be aggravated by exposure to this product.

PRIMARY ROUTE(S) OF ENTRY: ☒ DERMAL ☒ INHALATION ☐ INGESTION

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. Use artificial respiration if necessary. Seek medical attention.

SKIN CONTACT: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse.

EYE CONTACT: Immediately flush eyes with large amounts of water. If symptoms persist, seek medical attention.

INGESTION: Give 1 or 2 glasses of water to dilute. Do not induce vomiting. Get medical attention immediately.

SECTION 6 - REACTIVITY DATA

STABILITY: Stable **HAZARDOUS POLYMERIZATION:** Will not occur

INCOMPATIBILITY (Materials to avoid): Avoid contact with strong oxidizing agents.

SECTION 7 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources. Contain spill, absorb liquid with clay, sand or floor absorbent. Prevent run-off to sewers, streams or other bodies of water.

WASTE DISPOSAL METHOD: Observe all federal, state and local regulations regarding proper disposal.

SECTION 8 - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: NIOSH/MSHA jointly approved air purifying respirator if TLV limits are exceeded. Approved mechanical filter to remove solid airborne particles of overspray during application.

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV.

PROTECTIVE CLOTHING: Wear safety glasses with side shields to prevent eye contact. Contact lenses should not be worn. Use solvent resistant gloves to avoid prolonged contact.

OTHER PROTECTIVE EQUIPMENT: Eyewash fountains and safety showers in the event of an accident.

HYGIENIC PRACTICES: Wash hands thoroughly after use, and before eating, drinking or smoking.

SECTION 9 - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Handle as an extremely flammable material. Keep liquid and vapor away from heat, sparks, and open flame. Close container after each use. Store in a cool dry area. Do not expose container to temperatures above 120°F. To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in water-filled, closed metal container.

OTHER PRECAUTIONS: CAUTION: Keep out of reach of children. Containers should be grounded when pouring. Avoid free fall of more than 2 - 3 inches when pouring. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

The information contained in this MSDS is based on information and data provided by the supplier of the raw material used in the manufacture of this product. Although GPM believes such information and data to be reliable, GPM makes no warranty, expressed or implied, regarding the accuracy and completeness of such information and data.