



SAFETY DATA SHEET

1. Identification

| | |
|--|--|
| Product identifier | Heavy Duty Silicone - 11 oz |
| Other means of identification | |
| Product Code | No. 05174 (Item# 1003743) |
| Recommended use | Silicone-based multi-purpose lubricant |
| Recommended restrictions | None known. |
| Manufacturer/Importer/Supplier/Distributor information | |
| Manufactured or sold by: | |
| Company name | CRC Industries, Inc. |
| Address | 885 Louis Dr. Warminster, PA 18974 US |
| Telephone | 800-556-5074 |
| 24-Hour Emergency (CHEMTREC) | 800-424-9300 (US) |
| Website | crcindustries.com |

2. Hazard(s) identification

| | | |
|-----------------------|--|-----------------------------|
| Physical hazards | Flammable aerosols | Category 1 |
| | Gases under pressure | Liquefied gas |
| Health hazards | Skin corrosion/irritation | Category 2 |
| | Serious eye damage/eye irritation | Category 2A |
| | Specific target organ toxicity, single exposure | Category 3 narcotic effects |
| | Aspiration hazard | Category 1 |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard | Category 2 |
| | Hazardous to the aquatic environment, long-term hazard | Category 2 |
| OSHA defined hazards | Not classified. | |

Label elements



Signal word

Danger

Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapors. Wear eye protection/face protection. Wear protective gloves. Wash thoroughly after handling.

| | |
|--|--|
| Response | If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. |
| Storage | Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion. |
| Supplemental information | None. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|---|--------------------------|-------------|---------|
| acetone | | 67-64-1 | 15 - 40 |
| liquefied petroleum gas | | 68476-86-8 | 15 - 40 |
| naphtha (petroleum), hydrotreated light | | 64742-49-0 | 10 - 30 |
| heptane, branched, cyclic and linear | | 426260-76-6 | 3 - 7 |
| n-heptane | | 142-82-5 | 3 - 7 |
| solvent naphtha (petroleum), light aliph. | | 64742-89-8 | 1 - 5 |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|---|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell. |
| Skin contact | Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. |
| Ingestion | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Most important symptoms/effects, acute and delayed | Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Water fog. Alcohol resistant foam. Carbon dioxide (CO ₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |

| | |
|---|--|
| Fire-fighting equipment/instructions | In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes. |
| General fire hazards | Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. |

6. Accidental release measures

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination. |

7. Handling and storage

| | |
|---|--|
| Precautions for safe handling | Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label. |
| Conditions for safe storage, including any incompatibilities | Level 3 Aerosol. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

| | | |
|---|-------------|--------------|
| Occupational exposure limits The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits. | | |
| US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) | | |
| Components | Type | Value |
| acetone (CAS 67-64-1) | PEL | 2400 mg/m3 |
| | | 1000 ppm |
| naphtha (petroleum), hydrotreated light (CAS 64742-49-0) | PEL | 400 mg/m3 |
| | | 100 ppm |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|--|------|-----------------------|
| n-heptane (CAS 142-82-5) | PEL | 2000 mg/m3 500 ppm |
| solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) | PEL | 400 mg/m3 100 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|--------------------------|------|---------|
| acetone (CAS 67-64-1) | STEL | 500 ppm |
| | TWA | 250 ppm |
| n-heptane (CAS 142-82-5) | STEL | 500 ppm |
| | TWA | 400 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|--|---------|-----------------------|
| acetone (CAS 67-64-1) | TWA | 590 mg/m3 250 ppm |
| naphtha (petroleum), hydrotreated light (CAS 64742-49-0) | TWA | 400 mg/m3 100 ppm |
| n-heptane (CAS 142-82-5) | Ceiling | 1800 mg/m3 440 ppm |
| | TWA | 350 mg/m3 85 ppm |
| solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) | TWA | 400 mg/m3 100 ppm |

Biological limit values
ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------|---------|-------------|----------|---------------|
| acetone (CAS 67-64-1) | 25 mg/l | Acetone | Urine | * |

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Polyvinyl alcohol (PVA). Butyl rubber.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

| | |
|----------------|--------------|
| Physical state | Liquid. |
| Form | Aerosol. |
| Color | Water-white. |

Odor Solvent.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -139.6 °F (-95.4 °C) estimated

Initial boiling point and boiling range 132.8 °F (56 °C) estimated

Flash point -0.00004 °F (-17.8 °C) estimated

Evaporation rate Fast.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 1 % estimated

Explosive limit - upper (%) 14.3 % estimated

Vapor pressure 1612.8 hPa estimated

Vapor density >1 (air = 1)

Relative density 0.69 estimated

Solubility(ies)

Solubility (water) Slightly soluble.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 433 °F (222.8 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Other information

Percent volatile 80.2 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents.

Hazardous decomposition products Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

| Product | Species | Test Results |
|--|---------|------------------------------------|
| Heavy Duty Silicone - 11 oz | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | 3141 mg/kg |
| Inhalation | | |
| LC50 | Rat | 24 mg/l, 4 hours |
| Oral | | |
| LD50 | Rat | 4072 mg/kg |
| Components | Species | Test Results |
| acetone (CAS 67-64-1) | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | > 15800 mg/kg |
| Inhalation | | |
| LC50 | Rat | 76 mg/l, 4 Hours |
| Oral | | |
| LD50 | Rat | 5800 mg/kg |
| heptane, branched, cyclic and linear (CAS 426260-76-6) | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Inhalation | | |
| LC50 | Rat | > 60 mg/l, 4 hours |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| naphtha (petroleum), hydrotreated light (CAS 64742-49-0) | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rat | > 2000 mg/kg |
| Inhalation | | |
| Vapor | | |
| LC50 | Rat | > 5.2000000000000002 mg/l, 4 hours |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| n-heptane (CAS 142-82-5) | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Inhalation | | |
| LC50 | Rat | 103 mg/m3, 4 Hours |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | > 5 mg/kg |
| Inhalation | | |
| Vapor | | |
| LC50 | Rat | > 73.5 mg/l, 4 hours |

| Components | Species | Test Results |
|--|---|--------------|
| Oral LD50 | Rat | > 3000 mg/kg |
| Skin corrosion/irritation | Causes skin irritation. | |
| Serious eye damage/eye irritation | Causes serious eye irritation. | |
| Respiratory or skin sensitization | | |
| Respiratory sensitization | Based on available data, the classification criteria are not met. | |
| Skin sensitization | Based on available data, the classification criteria are not met. | |
| Germ cell mutagenicity | Based on available data, the classification criteria are not met. | |
| Carcinogenicity | Based on available data, the classification criteria are not met. | |
| IARC Monographs. Overall Evaluation of Carcinogenicity | | |
| Not listed. | | |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) | | |
| Not listed. | | |
| US. National Toxicology Program (NTP) Report on Carcinogens | | |
| Not listed. | | |
| Reproductive toxicity | Based on available data, the classification criteria are not met. | |
| Specific target organ toxicity - single exposure | May cause drowsiness or dizziness. | |
| Specific target organ toxicity - repeated exposure | Based on available data, the classification criteria are not met. | |
| Aspiration hazard | May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. | |
| Chronic effects | Prolonged inhalation may be harmful. | |

12. Ecological information

| | | |
|--|--|-----------|
| Ecotoxicity | Toxic to aquatic life with long lasting effects. | |
| Persistence and degradability | No data is available on the degradability of any ingredients in the mixture. | |
| Bioaccumulative potential | | |
| Partition coefficient n-octanol / water (log Kow) | | |
| acetone | | -0.24 |
| n-heptane | | 4.66 |
| Bioconcentration factor (BCF) | | |
| naphtha (petroleum), hydrotreated light | | 10 - 2500 |
| Mobility in soil | No data available. | |
| Other adverse effects | The product contains volatile organic compounds which have a photochemical ozone creation potential. | |

13. Disposal considerations

| | | |
|------------------------|--|--|
| Disposal instructions | If discarded, this product is considered a RCRA ignitable waste, D001. Full or partially-full aerosol cans can be treated as universal waste. Empty container can be recycled. Contents under pressure. Do not incinerate sealed containers. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations. | |
| Hazardous waste code | Possible RCRA waste code includes: D001: Waste Flammable material with a flash point <140 F | |
| | However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal. | |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. | |

14. Transport information

| | | |
|-------------------------|---------------------------------------|--|
| DOT | | |
| UN number | UN1950 | |
| UN proper shipping name | Aerosols, flammable, Limited Quantity | |

| | |
|-----------------------------------|---|
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Label(s) | 2.1 |
| Packing group | Not assigned. |
| Environmental hazards | |
| Marine pollutant | Yes, but exempt from the regulations. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Special provisions | N82 |
| Packaging exceptions | 306 |
| Packaging non bulk | 304 |
| Packaging bulk | None |


IATA

| | |
|-----------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | Aerosols, flammable, Limited Quantity |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Packing group | Not assigned. |
| ERG Code | 10L |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Other information | |
| Passenger and cargo aircraft | Allowed with restrictions. |
| Cargo aircraft only | Allowed with restrictions. |


IMDG

| | |
|-----------------------------------|---|
| UN number | UN1950 |
| UN proper shipping name | AEROSOLS, Limited Quantity |
| Transport hazard class(es) | |
| Class | 2.1 |
| Subsidiary risk | - |
| Packing group | Not assigned. |
| Environmental hazards | |
| Marine pollutant | Yes, but exempt from the regulations. |
| EmS | F-D, S-U |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

DOT; IMDG



IATA



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

acetone (CAS 67-64-1)

CERCLA Hazardous Substances: Reportable quantity

acetone (CAS 67-64-1) 5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

acetone (CAS 67-64-1) 6532

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

acetone (CAS 67-64-1) Low priority

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Gas under pressure
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Hazard not otherwise classified (HNOC)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)
Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)
Heptane (CAS 142-82-5)
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha (CAS 64742-49-0)
Solvent naphtha (petroleum), light aliph.; Low boiling point naphtha (CAS 64742-89-8)

US. New Jersey Worker and Community Right-to-Know Act

ACETONE (CAS 67-64-1)

NAPHTHA (CAS 64742-49-0)
NAPHTHA (CAS 64742-89-8)
N-HEPTANE (CAS 142-82-5)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)
Naphtha (CAS 64742-49-0)
Naphtha (CAS 64742-89-8)
n-Heptane (CAS 142-82-5)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Propanone (CAS 67-64-1)
Heptane (CAS 142-82-5)
Naphtha (CAS 64742-49-0)
Naphtha (CAS 64742-89-8)

US. Rhode Island RTK

ACETONE (CAS 67-64-1)
HEPTANE (CAS 142-82-5)
VM & P NAPHTHA (CAS 64742-49-0)
VM & P NAPHTHA (CAS 64742-89-8)

California Proposition 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance

| | |
|-----------------------------|---------------------------|
| acetaldehyde (CAS 75-07-0) | Listed: April 1, 1988 |
| benzene (CAS 71-43-2) | Listed: February 27, 1987 |
| cumene (CAS 98-82-8) | Listed: April 6, 2010 |
| ethylbenzene (CAS 100-41-4) | Listed: June 11, 2004 |
| naphthalene (CAS 91-20-3) | Listed: April 19, 2002 |

California Proposition 65 - CRT: Listed date/Developmental toxin

| | |
|------------------------|---------------------------|
| benzene (CAS 71-43-2) | Listed: December 26, 1997 |
| methanol (CAS 67-56-1) | Listed: March 16, 2012 |
| toluene (CAS 108-88-3) | Listed: January 1, 1991 |

California Proposition 65 - CRT: Listed date/Male reproductive toxin

| | |
|-------------------------|---------------------------|
| benzene (CAS 71-43-2) | Listed: December 26, 1997 |
| n-hexane (CAS 110-54-3) | Listed: December 15, 2017 |

Volatile organic compounds (VOC) regulations

EPA

| | |
|--|---------------|
| VOC content (40 CFR 51.100(s)) | 59.5 % |
| Consumer products (40 CFR 59, Subpt. C) | Not regulated |

State

| | |
|--------------------------|--|
| Consumer products | This product is regulated as a Silicone Based Multi-Purpose Lubricant. This product is compliant for use in all 50 states. |
| VOC content (CA) | 59.5 % |
| VOC content (OTC) | 59.5 % |

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia | Australian Inventory of Industrial Chemicals (AICIS) | No |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | No |

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|----------------------|--|
| Issue date | 01-13-2024 |
| Prepared by | Angelina Cibulskis |
| Version # | 01 |
| Further information | CRC # 519C/1002519 |
| Disclaimer | The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc.. |
| Revision information | This document has undergone significant changes and should be reviewed in its entirety. |