MATERIAL SAFETY DATA SHEET

Total Solutions P.O. Box 240014 Milwaukee, WI 53224

GENERAL INFORMATION NUMBER: (414) 354-6417 CHEMTREC: (800) 424-9300



REVISION DATE: January 11, 2012 DATE OF ISSUE: January 12, 2012

I - Product Identification							
Silicone Lube PRODUCT CODE: 8102 CHEMICAL FORMULATION: Pressur NFPA HAZARD IDENTIFICATION S HAZARD RATING: 4 - Extrem	YSTEM: HEALT	` H: 1	FLAMMA Moderate;		7 : 4 - Slight;		EACTIVITY :(0 - Insignificant
	II - Hazaro	dous Ingredi	ents				
	Values reported as TWA unless noted.						
SUBSTANCE Acetone	APPROX<u>%</u> 20.0-30.0	OSHA <u>PEL</u> 1000 ppm	ACGIH <u>TLV</u> 500 ppm	EP <u>302</u> Y	A 40 CI <u>355</u> N	F R: <u>372</u> N	<u>CAS #</u> 67-64-1
Propane	20.0-30.0	1000 ppm 1000 ppm	1000 ppm	N	N	N	74-98-6
n-Butane	20.0-30.0	N/E	1000 ppm 1000 ppm	N	N	N	106-97-8
Aliphatic Petroleum Solvent	10.0-15.0	N/E	N/E	N	N	N	64742-89-8
Synthetic Isoparaffinic Hydrocarbon	5.0 - 8.0	N/E	N/E	1,	11	1,	64742-47-8
372 : SARA TITLE III / List of T		hysical Data		•	-	,	
VAPOR PRESSURE (psig): 50.70 @ 70°F VAPOR DENSITY (AIR = 1): N/D		VOC C EVAPC pH: N/A	SPECIFIC GRAVITY (WATER = 1): 0.64 VOC CONTENT (% by weight): 60.0 EVAPORATION RATE (WATER = 1): N/D pH: N/A aydrocarbon odor.				
	IV - Fire and E	xplosion Haz	ard Data				
FLASH POINT (°F): -156 (propellant) FLAMMABLE LIMITS IN AIR (VOLU EXTINGUISHING MEDIA: Dry chemic SPECIAL FIRE FIGHTING PROCEDU protective gear including self-contained bre rupturing or venting containers. UNUSUAL FIRE AND EXPLOSION H 120° F may cause bursting.	cal, foam, carbon die J RES: Cool fire exp eathing apparatus. Us	: LOW oxide. NFPA osed containers se equipment or s	30B Rating: with water fog. shielding, as rec	Firefigh quired to	protect j	personn	el from bursting

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: Oxidizing agents

CONDITIONS TO AVOID: Heat, sparks, flames and electric arcs. Dropping of containers may cause bursting.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of carbon and hydrocarbon vapors. HAZARDOUS POLYMERIZATION: Will not occur.

VI - Health Hazard Data

ROUTES OF ENTRY INHALATION: X EYE CONTACT: SKIN CONTACT: INGESTION: INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None EFFECTS OF OVEREXPOSURE

IF IN EYES: Contact may irritate or burn eyes. Eye contact may result in corneal injury.

IF ON SKIN: Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Irritating to skin.

IF SWALLOWED: Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

IF INHALED: Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Irritating to respiratory system. Prolonged inhalation may be harmful.

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Flush with water for at least 15 minutes and remove contaminated clothing. Wash clothing separately before reuse. Obtain medical attention if irritation persists.

IF SWALLOWED: Contact physician or poison control center immediately. Do not induce vomiting unless instructed by a physician or poison control center. Do not leave individual unattended.

IF INHALED: Remove person to fresh air. If breathing has stopped, administer artificial respiration. Obtain medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate area. Remove all sources of ignition. Soak up material with inert absorbent material and place in a labeled container for disposal.

WASTE DISPOSAL METHOD: Consult local environmental authorities. Dispose of cans in non-incinerated trash only.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Use with adequate ventilation. Do not breathe vapors or mists. If recommended Exposure Limits are exceeded, wear a NIOSH approved respirator, following manufacturer's recommendations.

VENTILATION

LOCAL: Recommended

PROTECTIVE GLOVES: Chemical resistant.

EYE PROTECTION: Safety glasses.

OTHER PROTECTIVE EQUIPMENT: Protective clothing.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place away from heat, sparks or open flame. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Do not expose to direct sunlight or store at temperatures above 120 F.

OTHER PRECAUTIONS: Keep out of reach of children. Do not puncture or incinerate container.

IX - Transportation Information (ground transportation only)

DOT ID NUMBER: None DOT CLASS: ORM-D

DOT PROPER SHIPPING NAME: Consumer Commodity DOT PACKING GROUP: None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: January 11, 2012

Prepared by: Technical Dept.

DATE OF ISSUE: January 12, 2012

MECHANICAL: Not required

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Total Solutions assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.